



SHIEH YIH MACHINERY INDUSTRY CO., LTD. (HEADQUARTERS)

XIE YI TECH MACHINERY (CHINA) CO., LTD

SEYI-AMERICA, INC.

SEYI PRESSES EUROPE GmbH

www.seyi.com



SD SERIES

Solid Frame Crank Servo Press

SDG SERIES

Straight Side Crank Servo Press

SDE SERIES

Straight Side Eccentric Gear Servo Press

SEYI's Customized Total Solution for Our Valuable Customers




SEYI Servo Press + Transfer System + Feeder + Quick Die Change System

SEYI Servo Presses can easily integrate with different kinds of peripheral equipment, assisting our customers to achieve better production.

- | | | | |
|---|------------------|---|-------------------|
| 1 | SEYI Servo Press | 4 | Die Changing Cart |
| 2 | Feeder | 5 | Decoiler |
| 3 | Transfer System | 6 | Scrap Conveyor |



Scan me



Flexible and Capable to Meet Different Requirements


SEYI can provide a complete tandem line after a comprehensive evaluation of the customer's production method and environments. We provide systematic and flexible integrated solutions, including different types and tonnage presses to adapt to challenging requirements.

Our Advantages:

- Simultaneous / Cooperative control for multiple servo presses.
- The machine height of a tandem line would be lower than a single large press, lessening the factory construction cost.
- Servo and mechanical presses can be combined.

Take the small tonnage press line (at least 4 units) for example. The line not only matches the production in high tonnage, but also surpasses the productivity of a large-tonnage press. Customers do not need to prepare the foundation pit, saving the investment in factory construction.

By implementing a tandem line layout, the original transfer die configuration can be changed to one die, one station. This can effectively lessen eccentric load, which improves the quality of stampings, shortens the time for tool adjustments, and reduces the tool maintenance costs.



Small-tonnage press line Illustration




Scan me

SEYI's Eco-Friendly and Efficient Servo Press Benefits Customers

With an upward trend in environmental protection and power saving around the world, SEYI has been motivated by the mission to develop the world-class servo press. SEYI has utilized the latest technology in order to provide our customers with sophisticated, energy-saving and intelligent products. SEYI servo presses feature a direct drive transmission and a rigid frame design to reduce the total clearance. These presses are equipped with the most efficient servo motors that are only for servo presses.

Direct-Drive Transmission

- SEYI servo motors integrate the pinion shaft directly into the motor
- Accuracy exceeds JIS 1 level




Servo Motor

- Low Revolution Speed • High Torque
- Compact Size • High Efficiency
- Reduces power consumption
- Power regeneration
- Green equipment
- Excellent acceleration and deceleration
- The highest motor torque in the industry



Advanced Press Structure Enhancement- Perfect for New Materials

- SD Series-RIBBED frame design
Load balance to increase vertical and sidewall strength
- SDG/SDE Series -3 piece tie-rod frame structure
High rigidity suitable for high-tensile steel stamping



Energy Saving & Low Electrical Power Consumption

Compared with a traditional press, a SEYI servo press can provide significant savings on electricity costs.

	Servo Press	Mechanical Press	Hydraulic Press
Total Voltage	KVA	240	208
Power Consumption per Hour	kWh	48	83
Power Consumption per Year	kWh	359,000	622,000
Yearly Electricity Cost (Japan)	Yen (\$)	8,687,800	15,052,400
Yearly Electricity Cost (USA)	US (\$)	43,080	74,640
			174,120

*The calculation is based on a 1200ton servo press running 24 hours per day and 312 working days per year.


*The data is based on SEYI's assumptions. The actual expenses are subject to regions and applications.

User-Friendly Interface and Software

SEYI's user-friendly design on the HMI interface makes press operation simple and clear. Under each job number, all the corresponding parameters and settings, such as the motion profile, timing switches, tonnage monitor, die protection will be stored and saved in the servo press control system. When searching for a specific job number, all the settings for this tool will be shown on the HMI.

Easy-to-Use Interface

Operators can easily set the profile parameters in the system to optimize complex stamping processes.




Integrated Tonnage Monitor Function

- Set individual tonnage limits for each point and reverse tonnage limits
- Automatic setting of tonnage limits



Integrated Die Protection



*All specifications are subject to change without notice. Please check with your supplier for exact offers. Products may not be available in all markets.

- Supports NPN/PNP signals
- Set detection timing and type
- Set stop type (E-stop or Top stop)
- Timing switch to set up the timing zone for any specific functions

Stamping Samples By SEYI Servo Press

Twice the Productivity & Lower Power Consumption

Forming by pendulum mode-Half Motion




Half Motion:

By taking the advantages of the servo press and the servo motor, the stamping stroke can be shortened.

Compared to traditional presses, SEYI servo presses can eliminate unnecessary press movement, double the production output, and save about 50% on electrical power consumption while running progressive dies with Half Motion.

Extrusion: Better Formability of Special Materials

Forming by holding pressure- Hold Motion




Hold Motion:

- Suitable for cold and hot forming
- BDC accuracy of 0.01mm
- (Able to dwell at BDC for extended time)



Hold motion on the servo press is suitable for special materials such as aluminum alloys and perform much better than traditional presses. Multiple stations are not necessary to complete this operation. For example, this work piece only needs a single process.

7 Pre-programmed Motion Profiles and 1 Free Motion curve



Deep Drawing: High Accuracy and Quality

Forming by vibration-Vibration Motion





Vibration Motion:

- Especially suitable for deep drawing
- Available in all SEYI servo presses, regardless of tonnage
- Precise control of the vibration speed and range

Bending: Spring Back Effect Improvement

Forming by restriking-Free Motion



Free Motion:

The stamping curve can be set up by customers themselves based on the condition of different tools.

SD1 series

Model	SD1-80	SD1-160	SD1-200	SD1-300
Tonnage Capacity	tf 80	160	200	300
Stroke Length	mm 180	220	250	300
Strokes per Minute	S.P.M. ~80	~ 60	~ 50	~ 40
Tonnage Rating Point	mm 5	6	6	6
Die Height	mm 330	400	450	550
Slide Adjustment	mm 80	100	110	120
Slide Area (L.R. x F.B.)	mm x mm 700 x 460	900 x 580	1000 x 670	1150 x 800
Bolster Area (L.R. x F.B.)	mm x mm 950 x 680	1150 x 760	1300 x 870	1450 x 1050
Bolster Thickness	mm 140	165	180	200
Bolster Height (w/o Mounts)	mm 900	940	1020	1040
Slide Adjustment Motor	HP x P 0.5 x 4	1 x 4	1 x 4	2 x 4
Window Opening	mm x mm 680 x 280	760 x 350	870 x 400	1050 x 450
Required Floor Space	mm x mm 1961 x 2050	2161 x 2557	2224 x 2761	2414 x 3157
Total Height	mm 2962	3502	3819	4345
Upper Die Weight	kgf 300	500	800	1300
Required Air Pressure	kgf/cm ² 5	5	5	5
Total Weight	tf 14.5	20	25	37.5
Die Cushion	Capacity tf	6	8	10
	Stroke Length mm	95	110	130
	Die Cushion Area(L.RxF.B.) mm x mm	480x340	560x370	700x450


Standard Attachments

- Servo System
- Safety Brake System
- Electrical Overload Protection
- Tonnage Monitor
- Programmable Motion Profiles
- Job Storage Capacity - Up to 200
- Die Height Adjustment
- Slide Positon Adjustment (Handy Pulser)
- Portable Operation Stand
- Misfeed Socket 4 Set (2A,2B)
- Pneumatic ejector 1 Set
- Safety Light Curtain
- Oil Lubrication System
- Total/Preset/Batch/Maintenance Counter
- Anti Vibration Mounts
- Safety Block
- Die Lamp
- Tool Box

Optional Attachments

- Hydro-pneumatic Die Cushion
- Quick Die Change System
- Hydraulic Die Cushion
- Lamp Socket (1A)
- NDC (Servo Die Cushion)
- Rear Safety Guard

Slide Area & Bolster Area



SD2 series



Model	SD2-160	SD2-200	SD2-300	SD2-400	SD2-500
Tonnage Capacity	tf	160	200	300	400
Stroke Length	mm	220	250	300	350
Strokes per Minute	S.P.M.	~60	~50	~40	~40
Tonnage Rating Point	mm	6	6	6	6
Die Height	mm	450	500	600	650
Slide Adjustment	mm	100	110	120	130
Slide Area(L.R. x F.B.)	mm x mm	1620 x 580	1900 x 670	2280 x 800	2380 x 1000
Bolster Area (L.R. x F.B.)	mm x mm	1910 x 760	2200 x 870	2580 x 1050	2680 x 1200
Bolster Thickness	mm	160	170	200	200
Bolster Height (w/o Mounts)	mm	950	1000	1150	1250
Slide Adjustment Motor	HP x P	2 x 4	2 x 4	2 x 4	2 x 4
Window Opening	mm x mm	760 x 400	870 x 450	1050 x 500	1200 x 550
Required Floor Space	mm x mm	2921 x 2510	3099 x 2666	3519 x 3115	3733 x 3250
Total Height	mm	3573	3954	4589	4939
Upper Die Weight	kgf	800	1300	1800	2500
Required Air Pressure	kgf/cm ²	5	5	5	5
Total Weight	tf	27	32	50	64
Die	Capacity	8x2	10x2	14x2	14x2
Die	Stroke Length	110	130	140	140
Cushion	Die Cushion Area(L.RxF.B.)	560x370x2	700x450x2	700x450x2	700x450x2




Standard Attachments

- Servo System
- Safety Brake System
- Electrical Overload Protection
- Tonnage Monitor
- Programmable Motion Profiles
- Job Storage Capacity - Up to 200
- Die Height Adjustment
- Slide Position Adjustment(Handy Pulser)
- Portable Operation Stand
- Misfeed Socket 4 Set(2A,2B)
- Hydraulic Die Cushion
- Lamp Socket (1A)
- Oil Lubrication System
- Total/Preset/Batch/Maintenance Counter
- Anti Vibration Mounts
- Safety Block
- Pneumatic ejector 1 Set
- NDC (Servo Die Cushion)
- Die Lamp
- Safety Light Curtain
- Rear Safety Guard
- Tool Box

Optional Attachments

- Hydro-pneumatic Die Cushion
- Quick Die Change System

Slide Area & Bolster Area



Unit: mm

Model	SD2-160	SD2-200	SD2-300	SD2-400	SD2-500
Bolster	a	200	215	235	235
	a1	200	220	220	220
	b	150	160	290	290
	c	100	110	110	110
	d	50	100	100	100
	e	100	100	100	100
	f(L.R.xF.B.)	6x4x2	7x5x2	7x5x2	7x5x2
	Øg	32	32	32	32
	Øh	40	40	40	40
	j	10.5	10.5	10.5	10.5
Slide Area	n	28	28	28	28
	p	30	30	30	30
	q	20	20	20	20
	s	48	48	48	48
	A	200	215	235	235
	A1	200	220	220	220
	ØB	51	51	51	51
	C	400	500	450	582
	D	125	140	150	150

SDG2 series

Model		SDG2-400	SDG2-600	SDG2-800	SDG2-1000	SDG2-1200
Tonnage Capacity	tf	400	600	800	1000	1200
Stroke Length	mm	350	350	350	400	400
Strokes per Minute	S.P.M.	~50	~50	~50	~50	~50
Pendulum Motion Stroke Length	mm	100	100	100	140	140
Pendulum Motion Stroke per Minute	S.P.M.	~80	~80	~80	~80	~80
Tonnage Rating Point	mm	6.5	6.5	6.5	6.5	6.5
Die Height	mm	700	700	800	800	800
Slide Adjustment	mm	250	250	300	300	300
Slide Area (L.R. x F.B.)	1	2500×1400	2500×1550	2800×1550	3100×1550	3400×1550
	2	2800×1400	2800×1550	3100×1550	3400×1550	3700×1550
	3	3100×1400	3100×1550	3400×1550	3700×1550	4000×1550
	4	3400×1400	3400×1550	3700×1550	4000×1550	4300×1550
	5	3700×1400	3700×1550	4000×1550	4300×1550	4600×1550
	6	4000×1400	4000×1550	4300×1550	4600×1550	4900×1550
	7	4300×1400	4300×1550	4600×1550	4900×1550	5200×1550
	8	4600×1400	4600×1550	4900×1550	5200×1550	5500×1550
	9	4900×1400	4900×1550	5200×1550	5500×1550	5800×1550
	10	5200×1400	5200×1550	5500×1550	5800×1550	6100×1550
Bolster Area (L.R. x F.B.)	1	2500×1400	2500×1550	2800×1550	3100×1550	3400×1550
	2	2800×1400	2800×1550	3100×1550	3400×1550	3700×1550
	3	3100×1400	3100×1550	3400×1550	3700×1550	4000×1550
	4	3400×1400	3400×1550	3700×1550	4000×1550	4300×1550
	5	3700×1400	3700×1550	4000×1550	4300×1550	4600×1550
	6	4000×1400	4000×1550	4300×1550	4600×1550	4900×1550
	7	4300×1400	4300×1550	4600×1550	4900×1550	5200×1550
	8	4600×1400	4600×1550	4900×1550	5200×1550	5500×1550
	9	4900×1400	4900×1550	5200×1550	5500×1550	5800×1550
	10	5200×1400	5200×1550	5500×1550	5800×1550	6100×1550
Bolster Thickness	mm	180	250	250	250	300
Window Opening	Bolster Only	F.B. x T.B.	1100×600	1300×600	1500×700	1500×700
	Front to Back Rolling Bolster		1100×600	1300×600	1500×700	1500×700
	Left to Right Rolling Bolster		1700×800	1850×800	1850×900	1850×900
Upper Die Weight	kgf	4000	5000	5500	6000	7000
Required Air Pressure	kgf/cm ²	5	5	5	5	5
Bolster Height	Fixed Bolster	mm	850	850	850	850
	Rolling Bolster		660	660	660	740
Die Cushion	Type	Cylinder	Cylinder	Cylinder*	Cylinder*	Cylinder*
	Capacity	tf	60	100	120**	150
	Stroke Length	mm	200	200	220	220
	Adjustment	mm	200	200	220	220
Die Cushion Area (L.R. x F.B.)	1	2000×900	2000×950	2300×1300	2600×1300	2900×1300
	2	2300×900	2300×950	2600×1300	2900×1300	3200×1300
	3	2600×900	2600×950	2900×1300	3200×1300	3500×1300
	4	2900×900	2900×950	3200×1300	3500×1300	3800×1300

* For selecting 120T, 150T and 200T air cylinder die cushions, bolster area in FB should be at least 1700mm, cushion area in FB should be 1300mm.

** For SDG-800-1, only 100T die cushion is available .

※ This specification is subject to change without notice.

Standard Attachments

- Servo System
- Safety Brake System
- Motorized Slide Adjustment
- Tonnage Monitor
- Programmable Motion Profiles
- Job Storage Capacity - Up to 200
- Electronic Die Release
- Programmable Cam Switches
- Portable Operator Stand
- Electrical Overload Protection
- Automatic Recirculating Lubrication System
- Total Counter - 1 Set
- Preset Counter - 1 Set
- Maintenance Counter - 1 Set
- Misfeed Socket - 2 Sets
- Air Outlet - 2 Sets
- Air Ejector - 1 Set
- Anti-Repeat Safety Circuit
- Touch Panel
- Safety Fence
- Ladder
- Tool Box
- Die Lamp
- Embedded Operator Console
- Safety Light Curtain
- Anti Vibration Mounts
- Automatic Counter Balance Pressure Adjustment

Optional Attachments

- Die Cushion
- Die Cushion Stroke Adjustment
- Die Cushion Locking Device
- Die Cushion Pin Lifting Device
- Quick Die Change System
- Rolling Bolster
- Pressurized Air Supply
- Safety Door
- Safety Block
- Work Area Light for Front & Rear
- Remote Monitoring System



SDE2 series

Model		SDE2-400	SDE2-600	SDE2-800	SDE2-1000	SDE2 -1200	
Tonnage Capacity	tf	400	600	800	1000	1200	
Stroke Length	mm	600	600	800	800	800	
Strokes per Minute	S.P.M.	30	30	25	25	25	
Tonnage Rating Point	mm	13	13	13	13	13	
Die Height	mm	700	800	1000	1000	1100	
Slide Adjustment	mm	300	400	500	500	500	
Slide Area (L.R. x F.B.)	1	2500×1400	2500×1550	2800×1700	3100×1700	3400×1700	
	2	2800×1400	2800×1550	3100×1700	3400×1700	3700×1700	
	3	3100×1400	3100×1550	3400×1700	3700×1700	4000×1700	
	4	3400×1400	3400×1550	3700×1700	4000×1700	4300×1700	
	5	3700×1400	3700×1550	4000×1700	4300×1700	4600×1700	
Bolster Area (L.R. x F.B.)	1	2500×1400	2500×1550	2800×1700	3100×1700	3400×1700	
	2	2800×1400	2800×1550	3100×1700	3400×1700	3700×1700	
	3	3100×1400	3100×1550	3400×1700	3700×1700	4000×1700	
	4	3400×1400	3400×1550	3700×1700	4000×1700	4300×1700	
	5	3700×1400	3700×1550	4000×1700	4300×1700	4600×1700	
Bolster Thickness	mm	180	250	250	250	300	
Window Opening	Bolster Only	F.B. x T.B.	1200×600	1350×700	1500×900	1500×900	1500×1000
	Front to Back Rolling Bolster		1200×600	1350×700	1500×900	1500×900	1500×1000
	Left to Right Rolling Bolster		1700×800	1850×900	2000×1100	2000×1100	2000×1200
Upper Die Weight	kgf	5000	6000	7000	7000	8000	
Required Air Pressure	kgf/cm ²	5	5	5	5	5	
Bolster Height	Fixed Bolster	mm	850	850	850	850	850
	Rolling Bolster		660	660	660	740	740
Die Cushion	Type	Cylinder	Cylinder	Cylinder	Cylinder	Cylinder	
	Capacity	tf	60	100	120	150	150
	Stroke Length	mm	200	200	220	220	220
	Adjustment	mm	200	200	220	220	220
Die Cushion Area (L.R. x F.B.)	1	2000×900	2000×950	2300×1300	2600×1300	2900×1300	
	2	2300×900	2300×950	2600×1300	2900×1300	3200×1300	
	3	2600×900	2600×950	2900×1300	3200×1300	3500×1300	
	4	2900×900	2900×950	3200×1300	3500×1300	3800×1300	

※ This speciation is subject to change without notice.

Standard Attachments


- Servo System
- Safety Brake System
- Motorized Slide Adjustment
- Tonnage Monitor
- Programmable Motion Profiles
- Job Storage Capacity - Up to 200
- Electronic Die Release
- Programmable Cam Switches
- Portable Operator Stand
- Electrical Overload Protection
- Automatic Recirculating Lubrication System
- Total Counter - 1 Set
- Preset Counter - 1 Set
- Maintenance Counter - 1 Set
- Misfeed Socket - 2 Sets
- Air Outlet - 2 Sets
- Air Ejector - 1 Set
- Anti-Repeat Safety Circuit
- Touch Panel
- Safety Fence
- Ladder
- Tool Box
- Die Lamp
- Embedded Operator Console
- Safety Light Curtain
- Anti Vibration Mounts
- Automatic Counter Balance Pressure Adjustment

Optional Attachments


- Die Cushion
- Die Cushion Stroke Adjustment
- Die Cushion Locking Device
- Die Cushion Pin Lifting Device
- Quick Die Change System
- Rolling Bolster
- Pressurized Air Supply
- Safety Door
- Safety Block
- Work Area Light for Front & Rear
- Remote Monitoring System




Tonnage Curves




Working Energy




Pendulum Motion




Tonnage Curves




Working Energy



Pendulum Motion



SEYI Servo Press is your first step toward Smart Factory



SEYI's servo system is designed to assist our customers in moving towards smart manufacturing systems. Flexible and extendable software design makes our press more intelligent. Real-time press status monitoring and remote repair can be done from anywhere in the world. This can assist the customers, especially multinational corporations, to monitor their production status in different countries and enhance global management efficiency.

Production Monitoring & Troubleshooting

- Production status monitoring
- Machine status monitoring and error reporting
- Quick response for troubleshooting and tracking
- History management

Intelligent Systems & Preventive Maintenance

- Auto adjustment to the optimal production condition
- Die protection
- Quality control monitoring
- Self-diagnosis and alert system